

INDUSTRIAL COMPONENT DATA

FS 0,635/ 60-MV-R- 9,0 1332197 PHOENIX CONTACT SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FS 0,635/ 60-MV-R-9,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	FS 0,635/ 60-MV-R-9,0
Catalog number	1332197
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-A5A9FD9FF1
Generated	2026-08-04

Product Overview

FS 0,635/ 60-MV-R- 9,0 1332197 PHOENIX CONTACT SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Pin
Number of plug-in contact rows (EF006935)	2
Modular spacing contacts (EF007326)	0.635 mm
Modular spacing connections (EF006827)	0.635 mm
Rated current In (EF008250)	0.5 A
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Material of contact surface (EF004020)	Gold
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	0.9 mm
Material insulation body (EF007543)	Other
Housing colour (EF000136)	Black
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-55 °C

CONTINUED**Technical Specifications**

TECHNICAL ATTRIBUTE	VALUE
Type of banding (EF007011)	Other

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC, number of poles: 60, pitch: 0.635 mm, color: black, contact surface: Au, contact connection type: Male, mounting: SMD welding

SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC, number of poles: 60, pitch: 0.635 mm, colour: black, surface contacts: Gold

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FS 0,635/ 60-MV-R-9,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.