

**INDUSTRIAL COMPONENT DATA**

# FS 0,635/ 60-MV-R- 9,0 1332197 PHOENIX CONTACT SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FS 0,635/ 60-MV-R-9,0



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | FS 0,635/ 60-MV-R-9,0           |
| Catalog number  | 1332197                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-A5A9FD9FF1                   |
| Generated       | 2026-08-05                      |

## Product Overview

FS 0,635/ 60-MV-R- 9,0 1332197 PHOENIX CONTACT SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC..

**STRUCTURED PRODUCT DATA**

## Technical Specifications

| TECHNICAL ATTRIBUTE                                                      | VALUE           |
|--------------------------------------------------------------------------|-----------------|
| Connector model (EF007495)                                               | Fixed connector |
| Contact type (EF001587)                                                  | Pin             |
| Number of plug-in contact rows (EF006935)                                | 2               |
| Modular spacing contacts (EF007326)                                      | 0.635 mm        |
| Modular spacing connections (EF006827)                                   | 0.635 mm        |
| Rated current In (EF008250)                                              | 0.5 A           |
| Over voltage category (EF006785)                                         | III             |
| Pollution degree (EF006786)                                              | 2               |
| Material of contact surface (EF004020)                                   | Gold            |
| Type of electric connection (EF003961)                                   | Other           |
| Diameter connection pin (EF006823)                                       | 0.9 mm          |
| Material insulation body (EF007543)                                      | Other           |
| Housing colour (EF000136)                                                | Black           |
| Inflammability class of insulation material according to UL94 (EF002521) | V0              |
| Operating temperature (EF002393)                                         | -55 °C          |

**CONTINUED****Technical Specifications**

| TECHNICAL ATTRIBUTE        | VALUE |
|----------------------------|-------|
| Type of banding (EF007011) | Other |

**Classification & Catalog Path**

|              |                                        |
|--------------|----------------------------------------|
| eCl@ss 7.1   | 21043711                               |
| eCl@ss 8.0   | 21043711                               |
| eCl@ss 9.0   | 21043711                               |
| ETIM 5.0     | EC002246                               |
| ETIM 6.0     | EC002246                               |
| ETIM 7.0     | EC002246                               |
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

**Additional Product Information**

SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC, number of poles: 60, pitch: 0.635 mm, color: black, contact surface: Au, contact connection type: Male, mounting: SMD welding

SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC, number of poles: 60, pitch: 0.635 mm, colour: black, surface contacts: Gold

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / FS 0,635/ 60-MV-R-9,0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.