


INDUSTRIAL COMPONENT DATA

FTP 11+1 1029709 PHOENIX CONTACT Test plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTP 11+1



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTP 11+1
Catalog number	1029709
Category	Accessories/spare parts for terminals
Minimum order	1 Pcs
Document ID	EO-ECD8A7249A
Generated	2026-08-01

Product Overview

Test plug

Test connector, rated voltage: 400 V, rated current: 24 A, connection type: Screw connection, Sizing cross-section: 2.5 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 1029709

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626531526

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 12

Number of levels 1

Potentials 12

Nominal cross section 6 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum load current 24 A

Rated surge voltage 4 kV

Test surge voltage 5 kV

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.31 W

Maximum load current 24 A

Nominal current IN 24 A

Nominal voltage UN 400 V

Open side panel No

Dimensions

Pitch 8.2 mm

Connection data

Note The conductor cross section depends on the cable lug used

Connection method Screw connection

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 2.5 mm²

Min. AWG conductor cross section, flexible 20

Max. AWG conductor cross section, flexible 14

Mounting

Mounting type Insertion in base strip

Min. tightening torque of the test socket screw: 0.5 Nm

Max. tightening torque of the test socket screw: 0.6 Nm

Standards and Regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 4.027141118eCl@ss 4.127141118eCl@ss 5.027141118eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss
7.027141190eCl@ss 8.027141190eCl@ss 9.027141190

ETIM 3.0EC000901ETIM 4.0EC000901ETIM 5.0EC002255ETIM 6.0EC002848

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTP 11+1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.