

INDUSTRIAL COMPONENT DATA

FTP-3/4SL 1030004 PHOENIX CONTACT Test plug, nom. voltage: 400 V, number of positions: 4, width: 56.8 mm, he..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTP-3/4SL



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTP-3/4SL
Catalog number	1030004
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-F4A50E1D20
Generated	2026-08-04

Product Overview

Test plug, nom. voltage: 400 V, number of positions: 4, width: 56.8 mm, height: 98.2 mm, color: gray

Test plug, rated voltage: 400 V, rated current: 20 A, number of poles: 4, connection type: Connection by terminal, Sizing cross-section: 2.5 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 1030004

Packing unit 1

Catalog page Page 645 (C-1-2019)

GTIN 4055626532523

Custom tariff number 85366990

Drawings

Dimensions

Mounting

Classifications

General

Connection data

Standards and Regulations

Drawings

Circuit diagram

Back to topGeneral

Number of positions 4

Potentials 4

Nominal cross section 6 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.31 W

Maximum load current 20 A

Current I_{th} 20 A

Nominal voltage UN 400 V

Back to topDimensions

Width 56.8 mm

Length 96.8 mm

Height 98.2 mm

Pitch 8.2 mm

Back to topConnection data

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 2.5 mm²

Min. AWG conductor cross section, flexible 20

Max. AWG conductor cross section, flexible 14

Back to topMounting

Min. tightening torque of the test socket screw: 0.5 Nm

Max. tightening torque of the test socket screw: 0.6 Nm

Back to topStandards and Regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCl@ss

eCl@ss 5.1 27141100

eCl@ss 6.0 27141100

eCl@ss 7.0 27440313

eCl@ss 8.0 27440313

eCl@ss 9.0 27440313

Back to topETIM

ETIM 4.0 EC000897

ETIM 5.0 EC002255

ETIM 6.0 EC002255

ETIM 7.0 EC002255

Back to topUNSPSC

UNSPSC 13.2 39121410

UNSPSC 18.0 39121410

UNSPSC 19.0 39121410

UNSPSC 20.0 39121410

UNSPSC 21.0 39121410

Back to top

ETIM for 1030004 Terminal blocks (EC002555)

Feature Name

Feature Value

Rated voltage (EF000228)

400 V

Conn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTP-3/4SL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.