

INDUSTRIAL COMPONENT DATA

FTP-3/6SL GN/BU 1090787 PHOENIX CONTACT Test plug, nom. voltage: 400 V, number of positions: 6, width: 56.8 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTP-3/6SL GN/BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTP-3/6SL GN/BU
Catalog number	1090787
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-071CDCE4A3
Generated	2026-08-06

Product Overview

Test plug, nom. voltage: 400 V, number of positions: 6, width: 56.8 mm, height: 98.2 mm, color: Green/blue

Test connector, nominal voltage: 400 V, number of poles: 6, Dimensioning cross-section: 2.5 mm², colour: green/blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 1090787

Packing unit 1

Catalog page Page 645 (C-1-2019)

GTIN 4055626900452

Custom tariff number 85366990

General

Connection data

Standards and Regulations

Classifications

Dimensions

Mounting

Environmental Product Compliance

General

Number of positions 6
Nominal cross section 6 mm²
Color Green/blue
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 20 A
Current I_{th} 20 A
Nominal voltage UN 400 V
[Back to top](#)[Dimensions](#)
Width 56.8 mm
Length 96.8 mm
Height 98.2 mm
Pitch 8.2 mm
[Back to top](#)[Connection data](#)
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 14
[Back to top](#)[Mounting](#)
Min. tightening torque of the test socket screw: 0.5 Nm
Max. tightening torque of the test socket screw: 0.6 Nm
[Back to top](#)[Standards and Regulations](#)
Flammability rating according to UL 94 V0
[Back to top](#)[Environmental Product Compliance](#)
REACH SVHC Lead 7439-92-1
[Back to top](#)[Classifications](#)
[eCl@ss](#)
[eCl@ss 5.1 27141100](#)
[eCl@ss 6.0 27141100](#)
[eCl@ss 7.0 27440313](#)
[eCl@ss 8.0 27440313](#)
[eCl@ss 9.0 27440313](#)
[Back to top](#)[ETIM](#)
[ETIM 4.0 EC000897](#)
[ETIM 5.0 EC002255](#)
[ETIM 6.0 EC002255](#)
[ETIM 7.0 EC002255](#)
[Back to top](#)[UNSPSC](#)
[UNSPSC 13.2 39121410](#)
[UNSPSC 18.0 39121410](#)
[UNSPSC 19.0 39121410](#)
[UNSPSC 20.0 39121410](#)
[UNSPSC 21.0 39121410](#)
[Back to top](#)
[ETIM for 1090787 Terminal blocks \(EC002555\)](#)
[Feature Nam...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTP-3/6SL GN/BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.