

**INDUSTRIAL COMPONENT DATA**

# FTPC 11+1 3069267 PHOENIX CONTACT Test plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTPC 11+1



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | FTPC 11+1                |
| Catalog number  | 3069267                  |
| Category        | Test plug terminal block |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-508001CB69            |
| Generated       | 2026-08-01               |

## Product Overview

**Test plug**

Test connector, rated voltage: 400 V, rated current: 24 A, number of poles: 12, connection type: Screw connection, Sizing cross-section: 2.5 mm², color: gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Enclosures connectivity

## Additional Product Information

**Key Commercial Data**

Orderkey 3069267

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626380025

Weight per Piece (excluding packing) 466.300 g

Custom tariff number 85366990

Country of origin PL (Poland)

**General**

Number of positions 12

Potentials 12

Nominal cross section 6 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0  
Maximum load current 24 A  
Maximum power dissipation for nominal condition 1.31 W  
Maximum load current 24 A  
Nominal current IN 24 A  
Nominal voltage UN 400 V  
Insertion/withdrawal cycles mechanical 500  
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Note regarding shock protection When plugged in  
Result of surge voltage test Test passed  
Surge voltage test setpoint 4.8 kV  
Result of power-frequency withstand voltage test Test passed  
Power frequency withstand voltage setpoint 1.89 kV  
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed  
Result of bending test Test passed  
Bending test rotation speed 10 rpm  
Bending test turns 135  
Bending test conductor cross section/weight 0.2 mm<sup>2</sup> / 0.2 kg  
6 mm<sup>2</sup> / 1.4 kg  
10 mm<sup>2</sup> / 2 kg  
Tensile test result Test passed  
Conductor cross section tensile test 0.2 mm<sup>2</sup>  
Tractive force setpoint 10 N  
Conductor cross section tensile test 6 mm<sup>2</sup>  
Tractive force setpoint 80 N  
Conductor cross section tensile test 10 mm<sup>2</sup>  
Tractive force setpoint 90 N  
Result of tight fit on....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTPC 11+1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.