

**INDUSTRIAL COMPONENT DATA**

# FTPC-3/11S 3069940 PHOENIX CONTACT Test plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTPC-3/11S



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | FTPC-3/11S               |
| Catalog number  | 3069940                  |
| Category        | Test plug terminal block |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-F78D22E942            |
| Generated       | 2026-08-03               |

## Product Overview

Test plug

Test connector, rated voltage: 400 V, rated current: 20 A, number of poles: 11, Sizing cross-section: 2.5 mm<sup>2</sup>, color: gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      **PHOENIX CONTACT > Enclosures connectivity**

## Additional Product Information

Key Commercial Data

Orderkey 3069940

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 615 (C-1-2017)

GTIN 4055626389318

Weight per Piece (excluding packing) 9.990 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 11

Potentials 11

Nominal cross section 6 mm<sup>2</sup>

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.31 W

Maximum load current 20 A

Nominal current I<sub>N</sub> 20 A

Nominal voltage U<sub>N</sub> 400 V AC/DC

Dimensions

Width 121.2 mm

Length 86 mm

Pitch 8.2 mm

Connection data

Note The conductor cross section depends on the cable lug used

Conductor cross section flexible min. 0.5 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Min. AWG conductor cross section, flexible 20

Max. AWG conductor cross section, flexible 14

Mounting

Min. tightening torque of the test socket screw: 0.5 Nm

Max. tightening torque of the test socket screw: 0.6 Nm

Standards and Regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 5.127141120eCl@ss 6.027141141eCl@ss 7.027440313eCl@ss 8.027440313eCl@ss 9.027440313

ETIM 4.0EC000897ETIM 5.0EC002255ETIM 6.0EC002255

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTPC-3/11S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.