

**INDUSTRIAL COMPONENT DATA**

# DT 6/2,5-DREHSILA 250 (5X20) 3034264 PHOENIX CONTACT

## Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DT 6/2,5-DREHSILA 250 (5X20)



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | PHOENIX CONTACT              |
| MPN / Reference | DT 6/2,5-DREHSILA 250 (5X20) |
| Catalog number  | 3034264                      |
| Category        | Fuse terminal block          |
| Minimum order   | 25 Pcs                       |
| Document ID     | EO-623F29744B                |
| Generated       | 2026-08-02                   |

### Product Overview

Fuse modular terminal block

Fuse terminal block, for fuse cartridge G, cross-section: 0.5-10 mm<sup>2</sup>, AWG: 20-8, width: 12.2 mm, colour: black

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

### Additional Product Information

Key Commercial Data

Orderkey 3034264

Packing unit 25 pc

Minimum order quantity 25 pc

Catalog page Page 213 (CL-2009)

GTIN 4046356052818

Weight per Piece (excluding packing) 25.050 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 2.5 mm<sup>2</sup>

Color black

Insulating material PA  
Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 0.77 W  
Fuse G / 5 x 20  
Fuse type Glass / ceramics / ...  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
LED voltage range 110 V AC ... 250 V AC  
LED current range 0.5 mA ... 2.5 mA  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current 10 A (with 4 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 10 A  
Nominal voltage U<sub>N</sub> 500 V  
Connection in acc. with standard IEC 60947-7-1  
Maximum load current (upper level) 10 A  
Nominal current I<sub>N</sub>(upper level) 10 A  
Nominal voltage U<sub>N</sub> 500 V  
Open side panel No  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of sm...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DT 6/2,5-DREHSILA 250 (5X20) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.