

INDUSTRIAL COMPONENT DATA

UK 5-HESI 3004100 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HESI



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-HESI
Catalog number	3004100
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-A6E2817053
Generated	2026-07-29

Product Overview

Fuse modular terminal block

Fuse rail terminal, fuse type: Glass/ceramic/..., fuse type: G/5 x 20/5 x 25/5 x 30, nominal voltage: 800 V, nominal current: 6.3 A, number of poles: 1, connection type: Screw connection, Sizing section: 1 mm², cross-section: 0.2 mm²- 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20 / 5 x 25 / 5 x 30, nom. voltage: 800 V, nominal current: 6.3 A, number of positions: 1, connection method: Screw connection, Rated cross section: 1 mm², cross section: 0.2 mm²- 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataNotesNote regarding marking For terminal marking, please use marking material with 8.2 mm pitch.

Note regarding marking For lever marking, please use marking material with 6.2 mm pitch.

Product propertiesProduct type Fuse terminal block

Number of positions 1

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 09

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Fuse type Glass / ceramics / ...

Rated surge voltage 8 kV

Maximum power dissipation for nominal condition 1.02 W

Fuse G / 5 x 20 / 5 x 25 / 5 x 30

Connection data Number of connections per level 2

Nominal cross section 4 mm²

Level 1 above 1 below 1

Screw thread M3

Tightening torque 0.6 ... 0.8 Nm

Stripping length 8 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 60947-7-3

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²

Cross-section with insertion bridge, rigid 4 mm²

Cross-section with insertion bridge, flexible 4 mm²

2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²

2 conductors wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HESI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.