

INDUSTRIAL COMPONENT DATA

UK 5-HESILA 250 3004142 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HESILA 250



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-HESILA 250
Catalog number	3004142
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-2A322F298F
Generated	2026-07-31

Product Overview

Fuse modular terminal block

Fuse rail terminal, fuse type: Glass/ceramic/..., fuse type: G/5 x 20/5 x 25/5 x 30, nominal voltage: 800 V, nominal current: 6.3 A, number of poles: 1, connection type: Screw connection, Sizing section: 1 mm², cross-section: 0.2 mm²- 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

Fuse terminal, fuse type: Glass / ceramic / ..., fuse type: G / 5 x 20 / 5 x 25 / 5 x 30, rated voltage: 800 V, rated current: 6.3 A, number of poles: 1, connection type: screw connection, Dimensioning cross-section: 1 mm², cross-section: 0.2 mm²- 4 mm², mounting type: NS 35/7.5, NS 35/15, NS 32, colour: Black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3004142

Packing unit 50 pc

Catalog page Page 454 (C-1-2017)

GTIN 4017918090661

Weight per Piece (excluding packing) 19.620 g

Custom tariff number 85369095

Country of origin TR (Turkey)

General

Note For terminal marking, please use marking material with 8.2 mm pitch.

For lever marking, please use marking material with 6.2 mm pitch.

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.02 W

Fuse G / 5 x 20 / 5 x 25 / 5 x 30

Fuse type Glass / ceramics / ...

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

LED voltage range 110 V AC/DC ... 250 V AC/DC

LED current range 0.5 mA ... 1 mA

Connection in acc. with standard IEC 60947-7-3

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal current I_N 6.3 A

Nominal voltage U_N 800 V (As a fuse terminal block)

Connection in acc. with standard IEC 60947-7-3

Rated operating voltage 250 V

Open side panel No

Number of positions 1

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Oscillation, broadband noise test result Test passed

Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03

Test spectrum Service life test category 1, class B, body mounted

Test frequency f₁= 5 Hz to f₂...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HESILA 250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.