

## INDUSTRIAL COMPONENT DATA

# UK-SI BU 3118096 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK-SI BU



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | UK-SI BU            |
| Catalog number  | 3118096             |
| Category        | Fuse terminal block |
| Minimum order   | 50 Pcs              |
| Document ID     | EO-CACF39BC7B       |
| Generated       | 2026-07-31          |

## Product Overview

Fuse modular terminal block

Fuse terminal block for fuse cartridge G 5 x 20 and 5 x 25, cross-section: 0.2-4 mm<sup>2</sup>, width: 8.2 mm, colour: Blue

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3118096

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 460 (C-1-2017)

GTIN 4017918092870

Weight per Piece (excluding packing) 18.090 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm<sup>2</sup>

Color blue  
Insulating material PA  
Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 1.02 W  
Fuse G / 5 x 20 / 5 x 25  
Fuse type Glass / ceramics / ...  
Rated surge voltage 4 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current 6.3 A (is determined by the fuse used)  
Nominal current IN 6.3 A  
Nominal voltage UN 400 V (As a fuse terminal block)  
400 V (As a disconnect terminal block)  
Open side panel No  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (AST...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK-SI BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.