

INDUSTRIAL COMPONENT DATA

PTC 4-HESILED 60 (5X20) 3270205 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTC 4-HESILED 60 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTC 4-HESILED 60 (5X20)
Catalog number	3270205
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-1265C88264
Generated	2026-08-03

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 60 V, nominal current: 6.3 A, connection type: Push-in connection, 1st floor, Sizing cross-section: 1 mm², cross-section: 0.2 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3270205

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 95 (C-1-2017)

GTIN 4055626045481

Weight per Piece (excluding packing) 10.600 g

Custom tariff number 85369095

Country of origin CN (China)

General

Note The current is determined by the fuse used, the voltage by the selected LED.

If the fuse is faulty, the downstream circuit will not be disconnected.

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.6 W

Fuse G / 5 x 20

Fuse type Glass / ceramics / ...

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

LED voltage range 30 V AC/DC ... 60 V AC/DC

LED current range 0.4 mA ... 0.86 mA

Connection in acc. with standard IEC 60947-7-3

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal current I_N 6.3 A

Nominal voltage U_N 60 V

Open side panel Yes

Relative insulation....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTC 4-HESILED 60 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.