

INDUSTRIAL COMPONENT DATA

UK 10,3-HESI N 3048386 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-HESI N



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-HESI N
Catalog number	3048386
Category	Fuse terminal block
Minimum order	12 Pcs
Document ID	EO-EE6A21429D
Generated	2026-08-04

Product Overview

Fuse modular terminal block

Fuse rail terminal, fuse type: Ceramic, fuse type: 10.3 x 38 mm, nominal voltage: 690 V, nominal current: 32 A, connection type: Screw connection, Sizing cross-section: 16 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3048386

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 462 (C-1-2017)

GTIN 4017918976293

Weight per Piece (excluding packing) 50.590 g

Custom tariff number 85369095

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 2.43 W
Fuse 10:3 x 38 mm
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group III a
Connection in acc. with standard IEC 60947-1/-3
Maximum load current 32 A (the current and voltage are determined by the fuse)
Nominal current I_N 32 A (the current and voltage are determined by the fuse)
Nominal voltage U_N 690 V AC (the current and voltage are determined by the fuse)
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 120 °C
Dimensions
Width 18 mm
Length 81 mm
Height NS 35/7,5 65.5 mm
Height NS 35/15 73 mm
Connection data
Conductor cross section solid min. 1.5 mm²
Conductor cross section solid max. 25 mm²
Conductor cross section flexible min. 1.5 mm²
Conductor cross section flexible max. 16 mm²
Conductor cross se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-HESI N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.