


INDUSTRIAL COMPONENT DATA

FLKM 16/AO/SI/DV 2304445 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 16/AO/SI/DV



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 16/AO/SI/DV
Catalog number	2304445
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-24E82DB766
Generated	2026-07-31

Product Overview

Passive module
 Fuse module (for analogue Delta V control output cards)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data
 Orderkey 2304445
 Packing unit 1 pc
 Note Made to Order (non-returnable)
 Catalog page Page 481 (C-5-2017)
 GTIN 4017918981983
 Weight per Piece (excluding packing) 169.080 g
 Custom tariff number 85369010
 Country of origin DE (Germany)
 Dimensions
 Width 90 mm
 Height 90 mm
 Depth 68 mm
 Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage < 50 V AC

60 V DC

Max. perm. current (per branch) 50 mA (In delivered state, with one 50 mA fuse, max. 1 A permitted)

Number of positions 16

Status display No

Mounting position any

Assembly instructions In rows with zero spacing

Degree of protection IP00

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 16

Pitch 2.54 mm

Supported controller

Controller Emerson DeltaV

- suitable I/O card VE4005S2B3

Standards and Regulations

Standards/regulations DIN EN 50178

IEC 60664

Rated insulation voltage 63 V

Rated surge voltage 0.6 kV

Insulation Functional insulation

Degree of pollution 2

Overvoltage category II

Environmental Produc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 16/AO/SI/DV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.