

INDUSTRIAL COMPONENT DATA

UM-DELTA V/A/SI 5603256 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-DELTA V/A/SI



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-DELTA V/A/SI
Catalog number	5603256
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-F7BAB64071
Generated	2026-08-02

Product Overview

Passive module

Fuse module with separable test sockets and terminal blocks for connection screen (for analogue cards of the Delta V control)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 5603256

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 483 (C-5-2017)

GTIN 4017918955021

Weight per Piece (excluding packing) 239.100 g

Custom tariff number 85369010

Country of origin US (United States)

Dimensions

Width 61 mm

Height 126 mm

Depth 71 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 24 V DC

Max. perm. current (per branch) 50 mA (in as-supplied state, with one 50 mA fuse, max. 1 A permitted)

Number of positions 16

Mounting position any

Connection data for connection 1

Connection name Field level

Connection method Screw connection

Stripping length 7 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 1

Number of positions 16

Pitch 2.54 mm

Supported controller

Controller Emerson DeltaV

- suitable I/O card VE4003S2B4

VE4005S2B3

VE4003S3B5

Standards and Regulations

Connection in acc. with standard CUL

Standards/regulations IEC 60664

DIN EN 50178

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-DELTA V/A/SI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.