

INDUSTRIAL COMPONENT DATA

FUSE/NANO/10A/F-10PCS 2907426 PHOENIX CONTACT Fuse set

Brand: PHOENIX CONTACT | Manufacturer Part Number: FUSE/NANO/10A/F-10PCS



Manufacturer	PHOENIX CONTACT
MPN / Reference	FUSE/NANO/10A/F-10PCS
Catalog number	2907426
Category	Blade fuse
Minimum order	1 Pcs
Document ID	EO-5CA11D30B3
Generated	2026-08-06

Product Overview

Fuse set

Plug-in fuse (TE5®); Amperage Rating: 10 A; Firing Behavior: Fast (F)

Plug-in fuse (TE5®); nominal current: 10 A; tripping behavior: fast-blow (F)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataNotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

Product propertiesProduct type Fuse

Number of fuses in the set 10

Electrical propertiesTripping characteristic fast-blow (F)

Nominal voltage UN <= 125 V AC/DC

Nominal current IN 10 A

Fuse NANO

ETIM for 2907426 Circuit breakers and fuses (EC002298)

Feature Name

Feature Value

Nominal current (EF000001)

10 A

Release characteristic (EF000889)

Fast (F)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FUSE/NANO/10A/F-10PCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.