

**INDUSTRIAL COMPONENT DATA**

# P-FU 6,3X32 LA 250-EX 3046525 PHOENIX CONTACT Fuse plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-FU 6,3X32 LA 250-EX



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | P-FU 6,3X32 LA 250-EX         |
| Catalog number  | 3046525                       |
| Category        | Component plug terminal block |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-0BFC523279                 |
| Generated       | 2026-08-04                    |

## Product Overview

Fuse plug

Fuse holder, Before replacing the fuse G, remove the fuse holder head from the base terminal., rated current: 10 A, fuse type: G/6.3 x 32, color: black

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3046525

Packing unit 10 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 244 (C-1-2017)

GTIN 4046356919272

Weight per Piece (excluding packing) 6.560 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Note Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.

Number of levels 1

Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Area of application Machine building  
Plant engineering  
Dimensions  
Width 8.2 mm  
Length 40 mm  
General  
Fuse G / 6,3 x 32  
Fuse type Sand filled  
Degree of pollution 3  
Maximum power dissipation 1.6 W  
LED voltage range 110 V AC/DC ... 250 V AC/DC  
LED current range 0.41 mA ... 0.96 mA  
Maximum load current 10 A (the current is determined by the fuse used)  
Nominal current I<sub>N</sub> 10 A (the current is determined by the fuse used)  
Open side panel No  
Standards and Regulations  
Flammability rating according to UL 94 V0  
Environmental Product Compliance  
China RoHS Environmentally friendly use period: unlimited = EFUP-e  
No hazardous substances above threshold values  
Classifications  
eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027141145eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss  
7.027141149eCl@ss 8.027141149eCl@ss 9.027141149  
ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC000899ETIM 5.0EC002018ETIM 6.0EC002018  
UNSPSC 6.0130211812UNSPSC 7.090139121410UNSPSC 1139121411UNSPSC 12.0139121411UNSPSC  
13.239121409  
ETIM for 3046525 Term...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-FU 6,3X32 LA 250-EX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.