

INDUSTRIAL COMPONENT DATA

P-FU 5X20-EX 3036807 PHOENIX CONTACT Fuse plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-FU 5X20-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	P-FU 5X20-EX
Catalog number	3036807
Category	Component plug terminal block
Minimum order	10 Pcs
Document ID	EO-6BCC88C183
Generated	2026-08-04

Product Overview

Fuse plug

Fuse holder, Before replacing the G fuse, remove the fuse holder head from the base terminal., nominal voltage: 500 V, nominal current: 6.3 A, connection type: Plug-in connection, fuse type: G/5 x 20, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3036807

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 233 (C-1-2017)

GTIN 4046356919210

Weight per Piece (excluding packing) 3.800 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Note Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.

Number of levels 1

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Dimensions

Width 6.2 mm

Length 28 mm

General

Fuse G / 5 x 20

Fuse type Sand filled

Degree of pollution 3

Maximum power dissipation 1.6 W (Short-circuit and overload protection)

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal current IN 6.3 A (the current is determined by the fuse used)

Nominal voltage UN 500 V (if used as fuse terminal block)

500 V (if used as disconnect terminal block)

Open side panel No

Connection data

Connection method Plug connection

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027141145eCl@ss 5.127141100eCl@ss 6.027142000eCl@ss
7.027142001eCl@ss 8.027142001eCl@ss 9.027142001

ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC000899ETIM 5.0EC000035ETIM 6.0EC000035

UNSPSC 6.0130211811UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-FU 5X20-EX with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.