

INDUSTRIAL COMPONENT DATA

P-FU 5X20 LED 60-EX 3036823 PHOENIX CONTACT Fuse plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-FU 5X20 LED 60-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	P-FU 5X20 LED 60-EX
Catalog number	3036823
Category	Component plug terminal block
Minimum order	10 Pcs
Document ID	EO-D9CE1C8CE2
Generated	2026-08-02

Product Overview

Fuse plug

Fuse holder, Before replacing the G fuse, remove the fuse holder head from the base terminal., rated voltage: 500 V, rated current: 6.3 A, fuse type: G/5 x 20, color: black

Fuse plug, Before replacing fuse G, pull the fuse plug out of the base terminal., rated voltage: 500 V, rated current: 6.3 A, fuse type: G / 5 x 20, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3036823

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 233 (C-1-2017)

GTIN 4046356919234

Weight per Piece (excluding packing) 4.130 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Note Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.

Number of levels 1

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Dimensions

Width 6.2 mm

Length 28 mm

General

Fuse G / 5 x 20

Fuse type Sand filled

Degree of pollution 3

Maximum power dissipation 1.6 W

LED voltage range 30 V AC/DC ... 60 V AC/DC

LED current range 0.4 mA ... 0.86 mA

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal current I_N 6.3 A (the current is determined by the fuse used)

Open side panel No

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027141145eCl@ss 5.127141100eCl@ss 6.027142000eCl@ss
7.027142001eCl@ss 8.027142001eCl@ss 9.027142001

ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC000899ETIM 5.0EC000035ETIM 6.0EC000035

UNSPSC 6.0130211811UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 3036823 Terminal blocks (EC002018)

Feature Name

Feature Value

Width/gr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-FU 5X20 LED 60-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.