

INDUSTRIAL COMPONENT DATA

PT 4-HESILED 24 (5X20) 3211903 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-HESILED 24 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 4-HESILED 24 (5X20)
Catalog number	3211903
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-2F16FE3B9F
Generated	2026-07-29

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 6.3 A, connection type: Push-in connection, Sizing cross-section: 1 mm², cross-section: 0.2 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3211903

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 95 (C-1-2017)

GTIN 4046356482530

Weight per Piece (excluding packing) 13.740 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Note The current is determined by the fuse used, the voltage by the selected LED.

If the fuse is faulty, the downstream circuit will not be disconnected.

Number of levels 1
Number of connections 2
Nominal cross section 4 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Maximum power dissipation for nominal condition 1.6 W
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)
LED voltage range 12 V AC/DC ... 30 V AC/DC
LED current range 0.31 mA ... 0.95 mA
Connection in acc. with standard IEC 60947-7-3
Maximum load current 6.3 A (the current is determined by the fuse used)
Nominal current I_N 6.3 A
Nominal voltage U_N 24 V
Op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-HESILED 24 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.