

INDUSTRIAL COMPONENT DATA

ST 4-HESILED 60 (5X20) 3036550 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-HESILED 60 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-HESILED 60 (5X20)
Catalog number	3036550
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-8061EA5F43
Generated	2026-07-29

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 60 V, nominal current: 6.3 A, connection type: Spring connection, 1st floor, Sizing cross-section: 1 mm², cross-section: 0.08 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3036550

Packing unit 50 pc

Catalog page Page 177 (C-1-2017)

GTIN 4017918900571

Weight per Piece (excluding packing) 15.310 g

Custom tariff number 85369095

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.6 W
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)
LED voltage range 30 V AC/DC ... 60 V AC/DC
LED current range 0.4 mA ... 0.86 mA
Connection in acc. with standard IEC 60947-7-3
Maximum load current 6.3 A (the current is determined by the fuse used)
Nominal current I_N 6.3 A
Nominal voltage U_N 60 V
Open side panel No
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-HESILED 60 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.