

INDUSTRIAL COMPONENT DATA

G-INS-M40-M68N-SNES-S 1424546 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-M40-M68N-SNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-M40-M68N-SNES-S
Catalog number	1424546
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-715FA4BFF1
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screwed connection material: Stainless steel 1.4305, outer diameter of the cable 19 mm ... 28 mm, shielding: no, connection thread: M40 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1424546

Packing unit 1 pc

Catalog page Page 700 (C-2-2017)

GTIN 4055626374512

Weight per Piece (excluding packing) 161.500 g

Custom tariff number 73269098

Country of origin TR (Turkey)

Dimensions

Length 52.5 mm

Wrench size, union nut 46 mm

Wrench size, support 46 mm

Hexagon angular dimension 51.5 mm

Length of the connecting thread 9 mm

Feed-through hole diameter 40.1 mm ... 40.3 mm

External cable diameter 19 mm ... 28 mm

21 mm ... 28 mm (for UL 514 B)

Ambient conditions

Degree of protection IP68 (5 bar, 30 min.)

IP66

IP69

Ambient temperature (operation) -40 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material Stainless steel 1.4305

Material, insert Polyamide 6

Cable seal material Neoprene

Sealing material Perbunan (O-ring)

Shielded no

Thread type connection side M40 x 1.5

Thread type on connection side M40

Torque 17 Nm (Union nut)

17 Nm (Support sleeve)

15 Nm (for UL514 B: union nut)

Color silver

Impact category 4

Execution of the strain relief A

Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque

Manufacturer BIMED

Manufacturer Designation BMSC-E5

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127149109eCl@ss 6.027149100eCl@ss 7.02714910...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-M40-M68N-SNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.