

INDUSTRIAL COMPONENT DATA

G-INVEN-M12-M67N-NNES-S 1424538 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INVEN-M12-M67N-NNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INVEN-M12-M67N-NNES-S
Catalog number	1424538
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-4E05CB8B96
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, outer diameter of the cable 4 mm ... 7 mm, shielding: no, connection thread: M12 x 1.5, colour: silver, with pressure compensation element and O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1424538

Packing unit 1 pc

Catalog page Page 702 (C-2-2017)

GTIN 4055626374437

Weight per Piece (excluding packing) 29.100 g

Custom tariff number 74199990

Country of origin TR (Turkey)

Dimensions

Length 36.5 mm

Wrench size, union nut 17 mm

Wrench size, support 17 mm

Length of the connecting thread 6 mm

Feed-through hole diameter 12.1 mm ... 12.2 mm

External cable diameter 4 mm ... 7 mm

4 mm ... 8 mm (for UL 514 B)

Ambient conditions

Degree of protection IP67

IP66

Ambient temperature (operation) -20 °C ... 100 °C (static)

General

Type with pressure compensation element and flat gasket

No. of conductors 1

Cable gland material Nickel-plated brass

Cable seal material CR

Sealing material NBR (O-ring)

Shielded no

Thread type connection side M12 x 1.5

Thread type on connection side M12

Torque 6 Nm (Union nut)

6 Nm (Support sleeve)

3 Nm (for UL514 B: union nut / support)

Color silver

Impact category 5

Execution of the strain relief A

Air flow rate 25 (l/h at a pressure differential of 70 mbar)

Manufacturer BIMED

Manufacturer Designation BMBCVG-0S

Standards and Regulations

Halogen-free no

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127149109eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432

ETIM 5.0EC000441ETIM 6.0EC000441

ETIM for 1424538 Cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INVEN-M12-M67N-NNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.