

INDUSTRIAL COMPONENT DATA

PTDA 1,5/2,5-6-3,5/5,0 1701520 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTDA 1,5/2,5-6-3,5/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTDA 1,5/2,5-6-3,5/5,0
Catalog number	1701520
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-F307525AD2
Generated	2026-08-05

Product Overview

PCB terminal block

Terminal block for printed circuit board, number of poles per row: 6, family of items: PTDA 1.5/, pitch: 3.5 mm, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.5 mm, type of packaging: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1701520

Packing unit 1

GTIN 4046356542425

Custom tariff number 85369010

Dimensions

Length [l] 16 mm

Pitch 3.5 mm

Width [w] 22.4 mm

Height 16 mm

Height [h] 19.5 mm

Solder pin [P] 3.5 mm

Pin spacing 3.5 mm

Hole diameter 1.3 mm

General

Range of articles PTDA 1,5/

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 200 V

Rated voltage (III/2) 240 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 13.5 A

Nominal cross section 1.5 mm²

Solder pin surface

Stripping length 10 mm

Number of positions 6

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 1.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 0.5 mm²

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTDA 1,5/2,5-6-3,5/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.