

INDUSTRIAL COMPONENT DATA

GKDS/E- 2 BS:F445-074 1704729 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: GKDS/E-2 BS:F445-074



Manufacturer	PHOENIX CONTACT
MPN / Reference	GKDS/E-2 BS:F445-074
Catalog number	1704729
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-ED11266065
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 630 V, nominal cross-section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: GKDS/E, pitch: 7.5 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of soldering pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

PCB terminal block, nominal current: 24 A, nom. voltage: 630 V, pitch: 7.5 mm, number of positions: 2, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green
Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsQuick and convenient testing using integrated test optionTwo solder pins reduce the mechanical strain on the soldering spotsThe latching on the side enables various numbers of positions to be combinedKey

Commercial Data

Orderkey 1704729

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918249366

Weight per Piece (excluding packing) 8.200 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Range of articles GKDS/E

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 24 A

Nominal cross section 2.5 mm²

Solder pin surface Sn

Internal cylindrical gage A3

Stripping length 9 mm

Number of positions 2

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GKDS/E-2 BS:F445-074 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.