

INDUSTRIAL COMPONENT DATA

GMKDS 1,5/ 5-7,62 BD:N-L1 1723216 PHOENIX CONTACT

Printed circuit board terminal, rated current: 17.5 A, rat..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMKDS 1,5/ 5-7,62 BD:N-L1



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMKDS 1,5/ 5-7,62 BD:N-L1
Catalog number	1723216
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-AD6507EA77
Generated	2026-08-06

Product Overview

Printed circuit board terminal, rated current: 17.5 A, rated voltage (III/2): 630 V, rated cross-section: 1.5 mm², number of rows: 1, number of poles per row: 5, item family: GMKDS 1.5, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of soldering pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMKDS 1,5/ 5-7,62 BD:N-L1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.