

INDUSTRIAL COMPONENT DATA

TTC-6P-2X1-12DC-PT-I 2908202 PHOENIX CONTACT Surge protection, consisting of protective plug and base elemen..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TTC-6P-2X1-12DC-PT-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	TTC-6P-2X1-12DC-PT-I
Catalog number	2908202
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-1E4DC46AE5
Generated	2026-08-05

Product Overview

Surge protection, consisting of protective plug and base element, with integrated status indicator for two signal wires with common reference potential, e.g., Digital IN/OUT.

Surge protection, consisting of plug-in protection and base element, with integrated status indication for two signal conductors with common reference potential, e.g. digital INPUT/OUTPUT.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2908202

Packing unit 1 pc

Catalog page Page 128 (C-4-2019)

GTIN 4055626282862

Weight per Piece (excluding packing) 40.000 g

Custom tariff number 85363010

Country of origin DE (Germany)

Drawings

Ambient conditions

Protective circuit

Connection data

Environmental Product Compliance

Dimensions

General

Additional technical data

Standards and Regulations

Classifications

Drawings

Diagram

Dimensional drawing

Pictogram

Circuit diagram

Back to topDimensions

Height 105.8 mm

Width 6.2 mm +0.1 mm

Depth 100 mm (incl. DIN rail 7.5 mm)

Back to topAmbient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 %

Altitude ≤ 4000 m (amsl (above mean sea level))

Degree of protection IP20

Back to topGeneral

Housing material PBT

Flammability rating according to UL 94 V-0

Color traffic grey A RAL 7042

light grey RAL 7035

Mounting type DIN rail: TH 35 - 7.5 mm

Type DIN rail module, two-section, divisible

Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground

Back to topProtective circuit

IEC test classification C1

C2

C3

D1

Nominal voltage UN 12 V DC

Maximum continuous voltage UC 15 V DC

10 V AC

Rated current 600 mA (56 °C)

Operating effective current I_{Cat UC} ≤ 100 μA

Residual current I_{PE} ≤ 200 μA

Nominal discharge current I_{n(8/20)} μs (line-earth) 5 kA

Pulse discharge current I_{imp(10/350)} μs (line-earth) 0.5 kA

Total di...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TTC-6P-2X1-12DC-PT-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.