

INDUSTRIAL COMPONENT DATA

MKDSP 25/ 3-15,00 BD:3XSERD 1701306 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSP 25/ 3-15,00 BD:3XSERD



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSP 25/ 3-15,00 BD:3XSERD
Catalog number	1701306
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-17D937957E
Generated	2026-08-04

Product Overview

PCB terminal block

Terminal block for printed circuit board, rated current: 125 A, dimensioning voltage (III/2): 1000 V, nominal section: 35 mm², Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, article family: MKDSP 25, pitch: 15mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Driver/PCB connection direction: 0°, Color: green, Pin arrangement: Pin arrangement 2x2 linear, Pin length [P]: 4.5mm, Packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1701306

Packing unit 1

GTIN 4046356525480

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles MKDSP 25

Pitch 15 mm

Number of positions 3

Connection method Screw connection with tension sleeve

Drive form screw head Philipps recess with slotted Torx (H1L)
Screw thread M5
Mounting type Wave soldering
Pin layout Linear 2x2 pinning
Number of levels 1
Number of connections 3
Number of potentials 3
Electrical parameters
Rated current 125 A
Rated insulation voltage (III/2) 1000 V
Rated surge voltage (III/2) 8 kV
Connection capacity
Conductor cross section solid 0.5 mm² ... 35 mm²
Conductor cross section flexible 0.5 mm² ... 35 mm²
Conductor cross section AWG / kcmil 20 ... 2
Conductor cross section flexible, with ferrule without plastic sleeve 1 mm² ... 35 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 1.5 mm² ... 35 mm²
2 conductors with same cross section, solid 0.5 mm² ... 6 mm²
2 conductors with same cross section, flexible 0.5 mm² ... 6 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.5 mm² ... 4 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 16 mm²
Stripping length 18 mm
Torque 2.5 Nm ... 4.5 Nm ($\leq 25 \text{ mm}^2 = 2.5 \text{ Nm}$; $35 \text{ mm}^2 = 4.5 \text{ Nm}$)
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface ch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSP 25/ 3-15,00 BD:3XSERD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.