

INDUSTRIAL COMPONENT DATA

GMSTB 2,5/ 2-ST-7,62BD-2VPE500 1713922 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/ 2-ST-7,62BD-2VPE500



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTB 2,5/ 2-ST-7,62BD-2VPE500
Catalog number	1713922
Category	Cable connector
Minimum order	500 Pcs
Document ID	EO-44DC81C53E
Generated	2026-08-05

Product Overview

Plug

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: GMSTB 2.5/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1713922

Packing unit 1

GTIN 4055626337784

Custom tariff number 85366990

Dimensions

Width [w] 13.24 mm

Pitch 7.62 mm

Dimension a 7.62 mm

General

Range of articles GMSTB 2,5/..-ST

Number of positions 2

Connection method Screw connection with tension sleeve

Insulating material group I

Rated voltage (III/2) 630 V

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Flammability rating according to UL 94 V0

Screw thread M3

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

ETIM for 1713922 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

7.62 mm

Modular spacing connections (EF006827)

7.62 mm

Angle contact/conductor connection (EF007546)

Other

Rated current In (EF008250)

12 A

Rated voltage (EF000228)

630 V

Rated surge voltage (EF002993)

6 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/ 2-ST-7,62BD-2VPE500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.