

INDUSTRIAL COMPONENT DATA

SDDC 1,5/ 3-PV-3,5 1848655 PHOENIX CONTACT Direct connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SDDC 1,5/ 3-PV-3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SDDC 1,5/ 3-PV-3,5
Catalog number	1848655
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-59F832E75D
Generated	2026-08-05

Product Overview

Direct connector

Direct connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, number of potentials: 6, number of rows: 2, number of poles: 3, number of connections: 6, family of articles: SDDC 1.5/.. -PV, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: SKEDD - Direct connection system, conductor connection direction/printed circuit board: 90 °, pin arrangement: Double linear pin arrangement, plug-in system: SKEDD, lock: Snap lock, fixing type: Snap flange, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1848655

Packing unit 250 pc

Minimum order quantity 250 pc

Note Made to Order (non-returnable)

GTIN 4055626307121

Weight per Piece (excluding packing) 3.370 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 13.5 mm

Width [w] 17.8 mm

Height [h] 17.6 mm

Pitch 3.5 mm

Dimension a 7 mm

General

Range of articles SDDC 1,5/...-PV

Number of positions 3

Connection method Push-in spring connection

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 400 V

Nominal current I_N 8 A

Nominal cross section 1.5 mm²

Insulating material PA

Stripping length 8 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.2 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.2 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SDDC 1,5/ 3-PV-3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.