


## INDUSTRIAL COMPONENT DATA

# GMSTBA 2,5/ 5-G-7,62 GY 1726907 PHOENIX CONTACT

## Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTBA 2,5/ 5-G-7,62 GY



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | GMSTBA 2,5/ 5-G-7,62 GY         |
| Catalog number  | 1726907                         |
| Category        | Printed circuit board connector |
| Minimum order   | 50 Pcs                          |
| Document ID     | EO-D7E3B306CE                   |
| Generated       | 2026-08-05                      |

### Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, color: gray, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: GMSTBA 2,5/..-G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

PCB headers, nominal cross section: 2.5 mm<sup>2</sup>, color: gray, nominal current: 12 A, rated voltage (III/2): 630 V, contact surface: Sn, contact connection type: Pin, number of potentials: 5, number of rows: 1, number of positions: 5, number of connections: 5, product range: GMSTBA 2,5/..-G, pitch: 7.62 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.23 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family GMSTBA 2,5/..-G

Product line COMBICON Connectors M

Number of positions 5

Pitch 7.62 mm

Number of connections 5  
Number of rows 1  
Number of potentials 5  
Mounting flange without  
Pin layout Linear pinning  
Solder pins per potential 1  
Data management status  
Article revision 03  
Electrical propertiesNominal current  $I_N$  12 A  
Nominal voltage  $U_N$  630 V  
Contact resistance 1.4 m $\Omega$   
Rated voltage (III/3) 400 V  
Rated surge voltage (III/3) 6 kV  
Rated voltage (III/2) 630 V  
Rated surge voltage (III/2) 6 kV  
Rated voltage (II/2) 630 V  
Rated surge voltage (II/2) 6 kV  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface contact area (top layer) Tin (3 - 5  $\mu\text{m}$  Sn)  
Metal surface contact area (middle layer) Nickel (1.3 - 3  $\mu\text{m}$  Ni)  
Metal surface soldering area (top layer) Tin (3 - 5  $\mu\text{m}$  Sn)  
Metal surface soldering area (middle layer) Nickel (1.3 - 3  $\mu\text{m}$  Ni)  
Material data - housing  
Color (Housing) gray (7042)  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability index GWFI according to EN 60695-2-12 850  
Glow wire ignition temperature GWIT according to EN 60695-2-13 775  
Temperature for the ball pressure test according to EN 60695-10-2...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTBA 2,5/ 5-G-7,62 GY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.