

INDUSTRIAL COMPONENT DATA

GMSTBA 2,5 HC/ 4-G-7,62 RD 1714833 PHOENIX CONTACT

Housing base printed circuit board, number of poles: 4, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTBA 2,5 HC/ 4-G-7,62 RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTBA 2,5 HC/ 4-G-7,62 RD
Catalog number	1714833
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-6B1A0EB51A
Generated	2026-08-05

Product Overview

Housing base printed circuit board, number of poles: 4, pitch: 7.62 mm, color: red, surface of contact: Tin, assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: red, nominal current: 16 A, dimensioning voltage (III/2): 630 V, contact surface: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 4, family of articles: GMSTBA 2.5 HC/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.2 mm, Stecksystem: POWER COMBICON 2.5, Locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Socket for printed circuits, nominal current: 16 A, rated operating voltage (III/2): 630 V, number of poles: 4, pitch: 7,62 mm, color: red, surface of contact: Tin, assembly: Soldering wave

Commercial data

The code for the order One million seven hundred fourteen thousand eight hundred thirty three

Pieces/pack. 50 PCS

Sales key AABAAA -

The amount of minimum order 500 PCS

GTIN Four trillion fifty five billion six hundred twenty six million five hundred twenty nine thousand six hundred twenty two

Weight per piece (package included) 1,800 g

Number customs tariff Eighty five million three hundred sixty six thousand nine hundred thirty

Size

Length [l] 12 mm

Width 30.48 mm

Step 7,62 mm

Measure 22,86 mm

Width [w] 30.48 mm

Height [h] 11.8 mm

Mounting height 8.6 mm

Pin length solder 3.2 mm

The size of the shanks 1 x 1 mm

Length 12 mm

General

Family article GMSTBA 2,5 HC/..-G

Color red

N. of poles Four

Environmental Product Compliance

China RoHS Period for proper use: unlimited = EFUP-and

Any hazardous substances above the threshold values

Rankings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 9.0 Twenty seven million four hundred forty thousand four hundred two

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTBA 2,5 HC/ 4-G-7,62 RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.