

INDUSTRIAL COMPONENT DATA

GMSTBVA 2,5/ 3-G-7,62 VPE250 1706849 PHOENIX CONTACT

Base housing, rated current: 12 A, number of poles: 3, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTBVA 2,5/ 3-G-7,62 VPE250



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTBVA 2,5/ 3-G-7,62 VPE250
Catalog number	1706849
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-4BCEC95B73
Generated	2026-08-05

Product Overview

Base housing, rated current: 12 A, number of poles: 3, pitch: 7.62 mm, color: green, contact surface: Tin, mounting: Wave solder

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: GMSTBVA 2.5/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Header, nominal current: 12 A, number of positions: 3, pitch: 7.62 mm, color: green, contact surface: Tin, mounting: Wave soldering

Your advantages

Maximum flexibility when it comes to device design - one header for connectors with different connection technologiesWell-known mounting principle allows worldwide useLarger pitch for increased voltage requirementsClosed contour for optimum stability of the plug-in connectionVertical connection enables multi-row arrangement on the PCBKey Commercial Data

Orderkey 1706849

Packing unit 1

GTIN 4046356886642

Custom tariff number 85366930

General

Range of articles GMSTBVA 2,5/..-G

Rated voltage (III/3) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Color green

Number of positions 3

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

eCI@ss

eCI@ss 4.0 272607xx

eCI@ss 4.1 27260701

eCI@ss 5.0 27260701

eCI@ss 5.1 27260701

eCI@ss 6.0 27260704

eCI@ss 7.0 27440402

eCI@ss 8.0 27440402

eCI@ss 9.0 27440402

ETIM

ETIM 4.0 EC002637

ETIM 5.0 EC002637

ETIM 6.0 EC002637

UNSPSC

UNSPSC 6.01 30211810

UNSPSC 7.0901 39121409

UNSPSC 11 39121409

UNSPSC 12.01 39121409

UNSPSC 13.2 39121409

ETIM for 1706849 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

3

Number of plug-in conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTBVA 2,5/ 3-G-7,62 VPE250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.