

## INDUSTRIAL COMPONENT DATA

# GMVSTBR 2,5/ 3-ST-7,62 BK 1903122 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMVSTBR 2,5/ 3-ST-7,62 BK



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | PHOENIX CONTACT           |
| MPN / Reference | GMVSTBR 2,5/ 3-ST-7,62 BK |
| Catalog number  | 1903122                   |
| Category        | Cable connector           |
| Minimum order   | 50 Pcs                    |
| Document ID     | EO-8DF92CA371             |
| Generated       | 2026-08-04                |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm<sup>2</sup>, colour: black, rated current: 12 A, dimensioning voltage (III/2): 630 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, number of connections: 3, article family: GMVSTBR 2.5/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 90°, Stecksystem: CLASSIC COMBICON, Lock: without, type of packaging: boxed packaging

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 1903122

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918437954

Weight per Piece (excluding packing) 6.980 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 12.6 mm

Width [ w ] 20.82 mm

Height [ h ] 26 mm

Pitch 7.62 mm

Dimension a 15.24 mm

General

Range of articles GMVSTBR 2,5/..-ST

Number of positions 3

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 500 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm<sup>2</sup>

Connection data

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 2.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, solid max. 1 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 1.5 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic slee...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMVSTBR 2,5/ 3-ST-7,62 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.