

**INDUSTRIAL COMPONENT DATA**

# UCS 237-195-F-CCD 9005 2203456 PHOENIX CONTACT

## Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS 237-195-F-CCD 9005



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | PHOENIX CONTACT        |
| MPN / Reference | UCS 237-195-F-CCD 9005 |
| Catalog number  | 2203456                |
| Category        | Electronic enclosure   |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-67FD5AC934          |
| Generated       | 2026-08-06             |

### Product Overview

Electronic housing

Complete enclosure for printed circuit boards, fixed in angular inserts, includes housing halves, closed side walls, angular inserts with plate attachment, screws for housing and board fixing, black housing color with turquoise blue angular inserts

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 2203456

Packing unit 1 pc

GTIN 4055626403427

Weight per Piece (excluding packing) 742.000 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Type UCS 237-195-F-CCD 9005

Order No. 2203456

Housing type Universal housings

Type flat

Measurements

**Dimensional drawing**

Width [ w ] 237 mm

Height [ h ] 195 mm

Depth [ d ] 47 mm

Dimensions 211.8 mm x 169.8 mm (Maximum circuit board dimensions)

**Material specifications**

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material PC

**Ambient conditions**

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

**PCB data**

Number of PCB holders 1

Note on PCB holders This product is prepared for a printed-circuit board. Additional printed-circuit boards can be mounted using adhesive pads (accessories).

PCB thickness 0.8 mm ... 3 mm

Total PCB surface 36040 mm<sup>2</sup>

Type of PCB mount Bolt mounting

Power dissipation, single housing at 20 °C

Ambient temperature 20 °C

Reduction factor 1

Mounting position vertical

Power dissipation 31 W

Power dissipation, single housing at 30 °C

Ambient temperature 30 °C

Reduction factor 0.8

Mounting position vertical

Power dissipation 25.5 W

Power dissipation, single housing at 40 °C

Ambient temperature 40 °C

Reduction factor 0.65

Mounting position vertical

Power dissipation....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / UCS 237-195-F-CCD 9005 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.