

INDUSTRIAL COMPONENT DATA

GMVSTBR 2,5/ 8-ST-7,62 RD 1707606 PHOENIX CONTACT

Plug-in part, rated current: 12 A, number of poles: 8, pit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMVSTBR 2,5/ 8-ST-7,62 RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMVSTBR 2,5/ 8-ST-7,62 RD
Catalog number	1707606
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-B4E9285156
Generated	2026-08-05

Product Overview

Plug-in part, rated current: 12 A, number of poles: 8, pitch: 7.62 mm, connection type: Screw connection with traction capsule, color: red, contact surface: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: red, nominal current: 12 A, dimensioning voltage (III/2): 630 V, contact surface: Tin, contact type: Female connection, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, number of connections: 8, family of articles: GMVSTBR 2.5/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, driver/printed circuit board connection direction: 90°, Stecksyst.: CLASSIC COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Plug component, nominal current: 12 A, number of positions: 8, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, color: red, contact surface: Tin

Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceLarger pitch for increased voltage requirementsAllows connection of two conductorsKey Commercial Data

Orderkey 1707606

Packing unit 1

GTIN 4046356935364

Custom tariff number 85366990

General

Range of articles GMVSTBR 2,5/..-ST

Type of contact Female connector

Number of positions 8

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 500 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²**Connection data**Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²2 conductors with same cross section, solid max. 1 mm²

2 conductors with same cross section, strand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMVSTBR 2,5/ 8-ST-7,62 RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.