

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 5-5,08 BD:1-5 1875580 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 5-5,08 BD:1-5



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 5-5,08 BD:1-5
Catalog number	1875580
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-95FF08FC12
Generated	2026-08-05

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 13.5 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of potentials: 5, number of rows: 1, number of poles per row: 5, article family: MKDSN 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

PCB terminal block, rated current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 5, number of rows: 1, number of poles per row: 5, product series: MKDSN 1.5, pitch: 5.08 mm, connection type: Screw connection with cage, screw connection form: L Longitudinal slot, Mounting: Wave soldering, conductor/board connection direction: 0°, Color: Green, Pin Layout: Linear Pinning, Pin Length [P]: 3.5mm, Number of Solder Pins per Potential: 1, Package Type: Packed in Carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1875580

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918349226

Weight per Piece (excluding packing) 4.830 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description PCB terminal block

Range of articles MKDSN 1,5

Pitch 5.08 mm

Number of positions 5

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Screw thread M3

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Number of connections 5

Number of potentials 5

Electrical parameters

Rated current 13.5 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.14 mm² ... 1.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 26 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.5 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 0.75 mm²

Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / 1.9 mm

Stripping length 6 mm

Torque 0.5 Nm ... 0.6 Nm

Material data - contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 5-5,08 BD:1-5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.