

**INDUSTRIAL COMPONENT DATA**

# UKH 70-PE/S 3213141 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKH 70-PE/S



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | UKH 70-PE/S           |
| Catalog number  | 3213141               |
| Category        | Ground terminal block |
| Minimum order   | 10 Pcs                |
| Document ID     | EO-06F0408DA3         |
| Generated       | 2026-08-04            |

## Product Overview

Ground modular terminal block

Ground terminal, number of connections: 2, number of poles: 1, connection type: Screw connection, Sizing cross-section: 70 mm<sup>2</sup>, cross-section: 16 mm<sup>2</sup> - 95 mm<sup>2</sup>, fixing type: PE foot with fixing screw, M6, mounting class: NS 35/7.5, NS 35/15, NS 35/15-2.3, NS 32, color: yellow-green

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3213141

Packing unit 10 pc

Catalog page Page 259 (C-1-2017)

GTIN 4046356783446

Weight per Piece (excluding packing) 198.000 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of positions 1

Number of levels 1

Number of connections 2

Nominal cross section 70 mm<sup>2</sup>  
Color green-yellow  
Insulating material PA  
Flammability rating according to UL 94 V0  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Open side panel No  
Terminal block mounting 6 Nm ... 8 Nm (PE foot with mounting screw, M6)  
Oscillation, broadband noise test result Test passed  
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03  
Test spectrum Service life test category 1, class B, body mounted  
Test frequency f1= 5 Hz to f2= 150 Hz  
ASD level 1.857 (m/s<sup>2</sup>)<sup>2</sup>/Hz  
Acceleration 0,8 g  
Test duration per axis 5 h  
Test directions X-, Y- and Z-axis  
Shock test result Test passed  
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03  
Shock form Half-sine  
Acceleration 5 g  
Shock duration 30 ms  
Number of shocks per direction 3  
Test directions X-, Y- and Z-axis (pos. and neg.)  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKH 70-PE/S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.