


INDUSTRIAL COMPONENT DATA

UT 4-PE/L/MT 3214364 PHOENIX CONTACT Multi-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-PE/L/MT



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-PE/L/MT
Catalog number	3214364
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-ECEA42E6BE
Generated	2026-08-02

Product Overview

Multi-level terminal block

Multi-floor terminal block, nominal voltage: 500 V, nominal current: 28 A, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², connection type: Screw connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3214364

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 232 (C-1-2017)

GTIN 4046356895699

Weight per Piece (excluding packing) 32.030 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 5

Potentials 3

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)

Maximum load current 36 A (with 6 mm² conductor cross section)

Nominal current I_N 28 A

Nominal voltage U_N 500 V

Maximum load current 20 A (with 6 mm² conductor connection)

Nominal current I_N 20 A (with 4 mm² conductor cross section)

Nominal voltage U_N 500 V

Open side panel No

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Oscillation, broadband noise test result Test passed

Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03

Test spectrum Service life test category 1, class B, body mounted

Test frequency f₁= 5 Hz to f₂= 150 Hz

ASD level 0.964 (m/s²)²/Hz

Acceleration 0.58 g

Test duration per axis 5 h

Test directions X-, Y- and Z-axis

Shock test result Test passed

Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03

Shock form....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-PE/L/MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.