


INDUSTRIAL COMPONENT DATA

MSLKG 6 1410505 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSLKG 6



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSLKG 6
Catalog number	1410505
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-0AEE7E99EC
Generated	2026-08-03

Product Overview

Ground modular terminal block

Ground terminal, In a joint alignment with the pitch terminal of the same contour, a zone separator plate must be used for insulation voltages > 250 V, number of connections: 2, connection type: Screw connection, 1st level, cross-section: 0.5 mm² - 10 mm², fixing type: PE foot with fixing screw, M4, mounting type: NS 15, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1410505

Packing unit 50 pc

Catalog page Page 529 (C-1-2017)

GTIN 4017918021085

Weight per Piece (excluding packing) 17.240 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note When aligned with a feed-through terminal block of the same shape, a partition plate must be used for insulation voltages > 250 V

Number of levels 1

Number of connections 2
Nominal cross section 6 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Open side panel No
Terminal block mounting 1.5 Nm ... 1.8 Nm (PE foot with mounting screw, M4)
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Dimensions
Width 8.2 mm
Length 39 mm
Height NS 15 36 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-2
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 8
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 10
Conductor cross section fl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSLKG 6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.