


INDUSTRIAL COMPONENT DATA

UISLKG 16 0443052 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UISLKG 16



Manufacturer	PHOENIX CONTACT
MPN / Reference	UISLKG 16
Catalog number	0443052
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-4EC6097954
Generated	2026-07-28

Product Overview

Installation ground terminal block

Ground terminal for distribution, number of connections: 2, connection type: Screw connection, Dimensioning section: 16 mm², section: 2.5 mm² - 25 mm², fastening type: PE foot with fixing screw, M4, mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0443052

Packing unit 50 pc

Catalog page Page 506 (C-1-2017)

GTIN 4017918002299

Weight per Piece (excluding packing) 37.010 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 2.43 W
Connection in acc. with standard IEC 60947-7-2
Open side panel No
Terminal block mounting 1.5 Nm ... 1.8 Nm (PE foot with mounting screw, M4)
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Dimensions
Width 12 mm
Length 42.5 mm
Height NS 35/7,5 47 mm
Height NS 35/15 54.5 mm
Height NS 32 52 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Conductor cross section solid min. 2.5 mm²
Conductor cross section solid max. 25 mm²
Conductor cross section flexible min. 4 mm²
Conductor cross section flexible max. 16 mm²
Conductor cross section AWG min. 12
Conductor cross section AWG max. 3
Conductor cross section flexible, with ferrule without plastic sleeve min. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 1.5 mm²
Conductor cross....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UISLKG 16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.