

INDUSTRIAL COMPONENT DATA

UISLKG 35 0443065 PHOENIX CONTACT Installation ground terminal block, Screw connection, Cross section: 0.75 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UISLKG 35



Manufacturer	PHOENIX CONTACT
MPN / Reference	UISLKG 35
Catalog number	0443065
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-212F09F567
Generated	2026-08-02

Product Overview

Installation ground terminal block, Screw connection, Cross section: 0.75 mm²

Ground terminal block for distribution, For connection sections of 35 mm² / AWG 2 an NS 32 copper rail must be inserted...
o NS 35..., nominal voltage: 800 V, nominal current: 125 A, number of connections: 2, number of poles: 1, cross-section:
0.75 mm² - 35 mm², type of fixation: PE foot with fixing screw, M5, mounting class: NS 35/7.5, NS 35/15, NS 32, colour:
yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

General

Note Use an NS 32... or NS 35... copper DIN rail for connection cross sections of 35 mm²/2 AWG.

Number of levels 1

Number of connections 2

Nominal cross section 35 mm²

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V2

General

Rated surge voltage 8 kV

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-2

Open side panel nein

Number of positions 1

Dimensions

Width 15 mm

Length 55 mm

Height NS 35/7,5 51 mm

Height NS 35/15 58.5 mm

Height NS 32 56 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Conductor cross section solid min. 0.75 mm²

Conductor cross section solid max. 35 mm²

Conductor cross section flexible min. 0.75 mm²

Conductor cross section flexible max. 35 mm²

Conductor cross section AWG min. 18

Conductor cross section AWG max. 2

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.75 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 35 mm²

2 conductors with same cross section, solid min. 0.75 mm²

2 conductors with same cross section, solid max. 16 mm²

2 conductors with same cross section, stranded min. 0.75 mm²

2 conductors with same cross section, stranded max. 10 mm²

2 conductors with same cross section, stranded, ferrules without pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UISLKG 35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.