


INDUSTRIAL COMPONENT DATA

USLKG 3-1 0441106 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 3-1



Manufacturer	PHOENIX CONTACT
MPN / Reference	USLKG 3-1
Catalog number	0441106
Category	Ground terminal block
Minimum order	1 Pcs
Document ID	EO-4250AD7B7C
Generated	2026-08-03

Product Overview

Ground modular terminal block

Ground terminal, In a joint alignment with pitch terminals of the same contour, a cover for insulation voltages > 690 V must be inserted, number of connections: 2, number of poles: 1, type of connection: Screw connection, cross-section: 0.2 mm² - 4 mm², type of fixing: PE foot with fixing screw, M2.5, mounting class: NS 35/15-2.3, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0441106

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 425 (C-1-2017)

GTIN 4017918002176

Weight per Piece (excluding packing) 18.280 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Note When aligning with a feed-through terminal block with the same shape, an end cover must be interposed with insulation voltages of > 690 V

Number of positions 1
Number of levels 1
Number of connections 2
Nominal cross section 2.5 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Open side panel No
Terminal block mounting 0.5 Nm ... 0.6 Nm (PE foot with mounting screw, M2.5)
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 3-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.