

INDUSTRIAL COMPONENT DATA

USLKG 6 N 0442079 PHOENIX CONTACT Ground modular terminal block, Connection method: Screw connection, Number..

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 6 N



Manufacturer	PHOENIX CONTACT
MPN / Reference	USLKG 6 N
Catalog number	0442079
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-27E44E27EA
Generated	2026-08-03

Product Overview

Ground modular terminal block, Connection method: Screw connection, Number of positions: 1, Cross section: 0.2 mm²
Terminal block, number of connections: 2, connection type: Screw connection, cross-section: 0.2 mm² - 10 mm², fixing type:
PE foot with fixing screw, M4, mounting class: NS 35/7.5, NS 35/15, NS 32, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

General

Number of levels 1

Number of connections 2

Nominal cross section 6 mm²

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V0

General

Rated surge voltage 8 kV

Pollution degree 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-2

Open side panel nein

Number of positions 1

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Dimensions

Width 8.2 mm

Length 42.5 mm

Height 45.8 mm

Height NS 35/7,5 47 mm

Height NS 35/15 54.5 mm

Height NS 32 52 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Connection method Screw connection

Connection in acc. with standard IEC 60947-7-2

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 10 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 8

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 6 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 10

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 6 N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.