

INDUSTRIAL COMPONENT DATA

USLKG 95 0441041 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 95



Manufacturer	PHOENIX CONTACT
MPN / Reference	USLKG 95
Catalog number	0441041
Category	Ground terminal block
Minimum order	10 Pcs
Document ID	EO-A32A5EBBBE
Generated	2026-07-29

Product Overview

Ground modular terminal block

Terminal block, number of connections: 2, number of poles: 1, connection type: Screw connection, Sizing cross-section: 95 mm², cross-section: 25 mm² - 95 mm², fixing type: PE foot with fixing screw, M8, mounting type: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 0441041

Packing unit 10 pc

Catalog page Page 263 (C-1-2017)

GTIN 4017918002145

Weight per Piece (excluding packing) 318.100 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 1

Number of levels 1

Number of connections 2

Nominal cross section 95 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 7.54 W
Open side panel No
Terminal block mounting 15 Nm ... 20 Nm (PE foot with mounting screw, M8)
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Dimensions
Width 25 mm
Length 83 mm
Height NS 35/7,5 90 mm
Height NS 35/15 97.5 mm
Height NS 32 95 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-2
Conductor cross section solid min. 25 mm²
Conductor cross section solid max. 95 mm²
Conductor cross section AWG min. 4
Conductor cross section AWG max. 3/0
Conductor cross section flexible min. 35 mm²
Conductor cross section flexible max. 95 mm²
Min. AWG conductor cross section, flexible 4
Max. AWG conductor cross section, flexible 3/0
Conductor cross section flexible, with ferrule without plastic sleeve min. 35 mm²
Conductor c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 95 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.