

## INDUSTRIAL COMPONENT DATA

# USLKG 95 0441041 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 95



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | USLKG 95              |
| Catalog number  | 0441041               |
| Category        | Ground terminal block |
| Minimum order   | 10 Pcs                |
| Document ID     | EO-A32A5EBBBE         |
| Generated       | 2026-08-03            |

## Product Overview

Ground modular terminal block

Terminal block, number of connections: 2, number of poles: 1, connection type: Screw connection, Sizing cross-section: 95 mm<sup>2</sup>, cross-section: 25 mm<sup>2</sup> - 95 mm<sup>2</sup>, fixing type: PE foot with fixing screw, M8, mounting type: NS 35/7.5, NS 35/15, NS 32, color: yellow-green

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > Modular TBs |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0441041

Packing unit 10 pc

Catalog page Page 263 (C-1-2017)

GTIN 4017918002145

Weight per Piece (excluding packing) 318.100 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of positions 1

Number of levels 1

Number of connections 2

Nominal cross section 95 mm<sup>2</sup>

Color green-yellow

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 7.54 W

Open side panel No

Terminal block mounting 15 Nm ... 20 Nm (PE foot with mounting screw, M8)

Relative insulation material temperature index (Elec., UL 746 B) 125 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Dimensions

Width 25 mm

Length 83 mm

Height NS 35/7,5 90 mm

Height NS 35/15 97.5 mm

Height NS 32 95 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Connection method Screw connection

Connection in acc. with standard IEC 60947-7-2

Conductor cross section solid min. 25 mm<sup>2</sup>

Conductor cross section solid max. 95 mm<sup>2</sup>

Conductor cross section AWG min. 4

Conductor cross section AWG max. 3/0

Conductor cross section flexible min. 35 mm<sup>2</sup>

Conductor cross section flexible max. 95 mm<sup>2</sup>

Min. AWG conductor cross section, flexible 4

Max. AWG conductor cross section, flexible 3/0

Conductor cross section flexible, with ferrule without plastic sleeve min. 35 mm<sup>2</sup>

Conductor c...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 95 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.