

INDUSTRIAL COMPONENT DATA

UT 16-PE 3044212 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 16-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 16-PE
Catalog number	3044212
Category	Ground terminal block
Minimum order	1 Pcs
Document ID	EO-5133FB1801
Generated	2026-08-03

Product Overview

Ground modular terminal block

Ground terminal, number of connections: 2, connection type: Screw connection, Sizing cross-section: 16 mm², cross-section: 1.5 mm² - 25 mm², mounting class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3044212

Packing unit 50 pc

Catalog page Page 253 (C-1-2017)

GTIN 4017918977573

Weight per Piece (excluding packing) 46.850 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm²

Color green-yellow

Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Process industry
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Open side panel Yes
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 2, bogie-mounted
Test frequency $f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$
ASD level $6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$
Acceleration 3.12 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 30g
Shock duration 18 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 130°C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130°C
Static insulating material application in cold -60°C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 16-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.