

INDUSTRIAL COMPONENT DATA

GSMKDS 3/ 3-7,62 BDMC:BN 1093462 PHOENIX CONTACT

Terminal for printed circuit board, nominal current: 24 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GSMKDS 3/ 3-7,62 BDMC:BN



Manufacturer	PHOENIX CONTACT
MPN / Reference	GSMKDS 3/ 3-7,62 BDMC:BN
Catalog number	1093462
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-58C4334281
Generated	2026-08-03

Product Overview

Terminal for printed circuit board, nominal current: 24 A, pitch: 7.62 mm, number of poles: 3, type of connection: Connection by screw with capsule-traction, assembly: Soldering by wave direction for connection conductor/pcb: 55 °, color: green

Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 630 V, nominal cross-section: 2.5 mm², Number of rows: 1, Number of poles per row: 3, article family: GSMKDS 3, pitch: 7.62 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 55 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GSMKDS 3/ 3-7,62 BDMC:BN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.