


INDUSTRIAL COMPONENT DATA

US-PML-GHS100 (25X25) 1014288 PHOENIX CONTACT

Hazardous substances label

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-PML-GHS100 (25X25)



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-PML-GHS100 (25X25)
Catalog number	1014288
Category	Warning/signing plate
Minimum order	10 Pcs
Document ID	EO-F60EEC2D39
Generated	2026-08-04

Product Overview

Hazardous substances label

Hazardous substance sign, Card, red/white, pre-printed, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: glued, diameter: 0 mm, usable area: 25 x 25 mm, Number of individual indexes: 9

Hazardous substances label, Card, red/white, pre-printed, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD: Diamond, mounting type: adhesive, diameter: 0 mm, Number of individual labels: 9, text field height: 25 mm, text field width: 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Warning label unprinted

Area of application Hazardous substance labeling according to CLP/GHS regulation

Type Diamond

Data management status

Article revision 00

Marking

Number of individual labels 9

Printing Diamond

Identification technology Thermal transfer

DimensionsWidth 25 mm
Text field width 25.00 mm
Height 25 mm
Text field height 25.00 mm
Depth 0.09 mm
Length 25 mm
Diameter 0.00 mm
Min. material thickness 0.09 mm
Material specificationsColor multicolored
red (RAL 3001)
white (RAL 9010)
Material Polyester
Components Silicone-free
Environmental and real-life conditionsUV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 % (Storage in a dry and dark place in the original packaging is recommended)
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type adhesive
ETIM for 1014288 Auxiliary material (EC001777)
Feature Name
Feature Value
Width (EF000008)
25 mm
Height (EF000040)
25 mm
Diameter (EF000551)
0 mm
Colour (EF000007)
Red/white

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-PML-GHS100 (25X25) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.