

INDUSTRIAL COMPONENT DATA

HBUS 107,6-16P-1S DEV-KIT BK 2202545 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: HBUS 107,6-16P-1S DEV-KIT BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HBUS 107,6-16P-1S DEV-KIT BK
Catalog number	2202545
Category	Cable connector
Minimum order	1 Pcs
Document ID	EO-F70B37B92E
Generated	2026-08-05

Product Overview

Plug

Bus connector for connecting BC modules on the rail; suitable for BC DEV-KITS, contains HBUS 107.6 and pinstrip

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type DIN rail connector
Product family BC 107,6..
Number of positions 16
Pitch 2.54 mm
Data management status
Article revision 02
Electrical propertiesNominal current IN 3 A (Total current of 25 A max.)
Contact resistance 23.9 m?
Rated voltage (III/3) 30 V
Rated surge voltage (III/3) 0.8 kV
Rated voltage (III/2) 30 V
Rated surge voltage (III/2) 0.8 kV
Rated voltage (II/2) 100 V
Rated surge voltage (II/2) 0.8 kV

Material specificationsMaterial data - contact

Contact material Cu alloy

Surface characteristics Completely gold-plated

Material data - housing

Color (Housing) black (9005)

Insulating material PA

Insulating material group I

CTI according to IEC 60112 600

Flammability rating according to UL 94 V0

material specifications - connector

Color () ()

DimensionsPitch 2.54 mm

Width [w] 107.6 mm

MountingMounting type DIN rail mounting

Mechanical testsVisual inspection

Specification IEC 60512-1-1:2002-02

Result Test passed

Dimension check

Specification IEC 60512-1-2:2002-02

Result Test passed

Environmental and real-life conditionsVibration test

Specification IEC 60068-2-6:2007-12

Frequency 10 - 150 - 10 Hz

Sweep speed 1 octave/min

Amplitude 0.15 mm (10 Hz ... 58.1 Hz)

Acceleration 20 m/s²

Test duration per axis 2.5 h

Test directions X-, Y- and Z-axis (pos. and neg.)

Durability test

Specification IEC 60512-9-1:2010-03

Impulse withstand voltage at sea level 0.91 kV

Contact resistance R1 23.9 mΩ

Contact resistance R2 24 mΩ

Insertion/withdrawal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HBUS 107,6-16P-1S DEV-KIT BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.